

Length
Overall: 53' Inside: 52' - 2^{1/2}"

Width
Overall: 102^{3/8}" Inside: 96^{1/2}"

Height
Overall: 13'6" Inside: 103^{1/8}"

Door Opening
Width: 96^{1/8}" Height: 101^{1/8}"

Weight
13,480 +/- 3%

Capacity
Tandem Axle: 55,000 lbs.
Max Load Dist in 10' Span: 27,500 lbs.

Kingpin
AAR Rated, 36" Setting

Suspension & Subframe
Air-Ride Slide Rails 212"

Axles
25,000 lb. Capacity, Type 30/30
Chambers, 5.5 Slacks, 16.5"x7"
Brakes, ABS 2S/1M

Wheels
8.25" x 22.5" Prepainted White Disc

Tires
295/75R 22.5

Landing Gear
2 Speed 50,000lb Capacity

Rear Under-Ride Guard
Carbon Steel with Anti-Slip

Crossmembers
4" Steel I-Beams on 12" Centers

Floors
1^{1/4}" Aluminum Heavy Duty Duct
.140" / ⁷/₅₀ Thickness

Floor Furring
Composite Material produced from Ethylene

Side Panels
.040" / ¹/₂₅ Aluminum Prepainted White Corrugated

Side Posts
2" Aluminum "Z" Post on 12" and 24" centers

Roof Bows
Extruded Aluminum on 24" centers

Roof Sheet
.032" / ⁴/₁₂₅" Aluminum

Rear Doors
Quilted Stainless Steel swing doors with (4) Hinges
and (1) lock-rod per door Door Insulation: 3"

Lining
Front: .090" / ⁹/₁₀₀" Fiberglass
Sides: .090" / ⁹/₁₀₀" Fiberglass
Ceiling: .060" / ³/₅₀" Fiberglass

Scuffband:
Extruded Aluminum, 11" High, Full length
Inside Width Scuff to Scuff 95¹⁵/₁₆

Insulation
Front: 3"
Sides: 2¹/₂"
Ceiling: 3"
Floor: 2³/₄"
Door: 3"

Forklift Package
48" Deep

Lights
LED and Incandescent Package



LITEGUARD 5000

REEFER



THE DORSEY WAY

- Excellence is our standard in all that we do.
- Providing superior value to our customers through quality products
- Maintaining the highest standards of ethics and integrity.
- People make the critical difference separating us from all competitors

FEATURES



Standard Stainless Rear Frame, Galvanized Door Locks, Stainless Quilted Rear Doors, LED Light Package Rear Header and Bumper



Optional Stainless Steel Door Locks



Standard 4-Bolt Hinges - (4) Four per Door with Integrated Bumper



Standard 11" Heavy Duty Scuff Welded at Rear



Standard Rubber Bumper Blocks and Rear Gusset



Optional Quad Hardware Door Locks



Standard Suspension, Air Ride Slider W/Aluminum Optional Color Corrosion Resistant Paint




Optional 4" Aluminum Crossmembers with Integrated Electrical and Airlines for max protection



Foam in Place Roof to Side Adhesion



Optional Shallow Rear Door Header



Standard/Composite Stringers, Composite Load Plate, Steel Approach Plate



Standard Heavy Duty Duct Type Floor



Optional Tuck Away Liftgate



Optional Stainless Steel Door Vent



Standard Aluminum Cove Molding used in Corner Closures for Greater Insulation



Optional Dock Board Guide Plates



Smooth Insulated Side Walls and Ceiling lined with Fiberglass



Standard Two-Speed Landing Gear 50,000 lb capacity



Optional Pull-out Platform and Step



Optional Roll-Up Door Pictured with painted rear frame



Optional Dome Lights and Surface Mounted E-Track



Optional Side Doors



Optional Customized Floor System